

VIAVI

SmartPocket Optical Test Kits

OMK-34/35/36/38

VIAVI Solutions® SmartPocket™ optical test kits (OMK-3x) are the new generation of pocket-sized and rugged instruments for installing and maintaining fiber optic networks. All test kits are equipped with an optical power meter and a dual or quad-wavelength optical light source dedicated to power level, insertion loss measurements, and continuity checks.

Rugged Field Design and Flexible Optical Interface

A lightweight, shock-resistant splash-proof design and an extended operating time make OMK-3x test kits ideal solutions for field use. A switchable adapter system on the light source with a universal push pull (UPP) adapter on the power meter that handles all 2.5 mm connectors (1.25 mm as optional accessory) make OMK-3x test kit ready for every connector type in the field.

Auto-λ Recognition Mode and TwinTest Mode

Auto-λ is a special feature developed by VIAVI to identify wavelengths automatically, helping avoid any manipulation errors due to incorrect settings.

In TWINTest mode, the source automatically toggles between two wavelengths. The far end optical power meter automatically measures both wavelengths.

Network Documentation and Certification

All VIAVI SmartPocket optical power meters provide result storage capability of up to 100 results. A micro USB port provides straightforward downloading using SmartReporter software. This software offers PDF or Excel report generation with pass/fail analysis against customized or industry standard thresholds.

Key Features

- Essential optical test kits for enterprise and service provider applications
- Certify standard, high dynamic, and high power applications
- Auto-wavelength and TWINTest features for error-free and efficient testing
- Permanent reference-level storage
- Fast result download and report generation with SmartReporter freeware

Applications

- Optical power level and link Insertion loss measurements for:
 - Enterprise/LAN networks with 850/1300 nm multimode wavelength capability
 - Access and metro (LAN/WAN) networks with multimode and single-mode testing combinations
 - Standard and high power level testing for telecom, CATV, and military applications
- Continuity checking and tone detection



The Right Kit for Every Application

Instruments					Applications				
		Light Source	Power Meter	Wavelength	MM*	SM*	Access/ FTTx	Metro/ Core	LAN/WAN Enterprise
Enterprise	OMK-34	OLS-34	OLP-34	850/1300 nm	✓				✓
	OMK-36	OLS-36	OLP-35	850/1300 nm 1310/1550 nm	✓	✓	✓	✓	✓
Service Providers	OMK-35	OLS-35	OLP-35	1310/1550 nm		✓	✓	✓	
	OMK-38	OLS-35	OLP-38	1310/1550 nm		✓	✓ Video overlay	✓ CATV	

* MM = multimode
SM = single-mode



OMK-3x kit with light source, power meter, power supply, and USB cable.

VIAVI OMK-3x optical test kits provide essential tools for power and insertion loss measurement and are ideal for a wide range of installation and maintenance applications.

OMK-34

The OMK-34 is a dual-wavelength multimode optical test kit with a single-port LED source and a power meter with a universal push/pull adapter (UPP) interface for power level and loss measurement in LAN and enterprise environments.

OMK-35

The VIAVI OMK-35 is a dual-wavelength single-mode optical test kit with a single-port laser source and a power meter with a UPP interface for power level and loss test measurement in access, metro, and core networks.

OMK-36

The VIAVI OMK-36 is an all purpose quad-wavelength optical test kit with a dual-port multimode/singlemode light source and a power meter with a UPP interface for all single-mode and multimode power and loss measurements.

OMK-38

The VIAVI OMK-38 is a dual-wavelength single-mode optical test kit with a single-port laser source and a power meter with a UPP interface for high power level and loss measurement in high-power networks and amplified network applications.

Technical Specifications

	OMK-34 Enterprise Kit	OMK-36 Enterprise Quad Kit	OMK-35 Service Provider Kit	OMK-38 Service Provider Hi- Power Kit
Light Source	OLS-34	OLS-36	OLS-35	OLS-35
Fiber type	MM (50/125 μm)	MM (50/125 μm)/SM	SM	SM
Output power	-22 dBm	-22 dBm/-7 dBm	-7 dBm	-7 dBm
Wavelength uncertainty	± 20 nm			
Connector type	Switchable adapters			
Power Meter	OLP-34	OLP-35	OLP-35	OLP-38
Power range	-60 to +5 dBm	-65 to +10 dBm	-65 to +10 dBm	-50 to +26 dBm
Max. input power	+13 dBm	+16 dBm	+16 dBm	+27 dBm
Connector type	Universal push pull (UPP), interface 2.5 mm (1.25 mm as accessory)			
Data storage	100 results			
General Loss Test Set Specifications				
Wavelength	850 nm	X	X	
	1300 nm	X	X	
	1310 nm		X	X
	1550 nm		X	X
Loss dynamic range	40 dB	40/58 dB	58 dB	43 dB
General Specifications				
Dimension (w x h x d)	280 x 215 x 50 mm (11 x 8.5 x 2 in)			
Weight	0.6 kg (1.32 lb)			

All OMK-3x kits include:

- A power meter with USB port (download capability and AC powering)
- A light source with switchable adapter (SC/PC mounted and FC/PC as a spare part)

Ordering Information

Description	Reference
Smart Pocket Test Kits	
OMK-34P Enterprise Plus- MM SmartPocket Test Kit with USB port	2127/01
OMK-36P Enterprise Plus- SM/MM SmartPocket Test Kit with USB port	2127/04
OMK-35P Service Provider Plus- SM SmartPocket Test Kit with USB port	2127/02
OMK-38P Service Provider Hi-Power Plus- SM SmartPocket Test Kit with USB port	2127/03

Each kit comes with AA alkaline batteries, AC power adapter, USB cable, operating manual, neck strap, soft case MT-2P.

Description	Reference
Optional Accessories	
Fiber Cleaning Consumables kit	FCR-CLN-01
NiMH rechargeable batteries, Mignon AA, 1.2V (2 batteries required)	2237/90.02
SNT-505; universal AC power adapter, micro USB connector	2302/90.01
Neck strap for SmartPocket	2302/90.03
USB connection cable	K807
MT-2P, soft case for 2 SmartPockets and accessories	2127/90.01
ST switchable adapter	2155/00.32
FC switchable adapter	2155/00.05
SC switchable adapter	2155/00.06
LC switchable adapter	2155/00.07
UPP adapter for LC ,MU (1.25 mm)	2256/90.03
SmartReporter Reporting Software (free download from http://smartreporter.updatemyunit.net/)	

VIAVI Care Support Plans

Increase your productivity for up to 5 years with optional VIAVI Care Support Plans:

- Maximize your time with on-demand training, priority technical application support and rapid service.
- Maintain your equipment for peak performance at a low, predictable cost.

For more Information: go to viavisolutions.com/viavicareplan

Features

*5-year plans only

Plan	Objective	Technical Assistance	Factory Repair	Priority Service	Self-paced Training	5 Year Battery and Bag Coverage	Factory Calibration
 BronzeCare	Technician Efficiency	Premium	✓	✓	✓		
 SilverCare	Maintenance & Measurement Accuracy	Premium	✓	✓	✓	✓*	✓



Contact Us **+1 844 GO VIAVI**
(+1 844 468 4284)

To reach the VIAVI office nearest you,
visit viavisolutions.com/contact

© 2020 VIAVI Solutions Inc.
Product specifications and descriptions in this document are subject to change without notice.
omk-3x-ds-fop-tm-ae
30162964 906 0120